

GONGDA GROUP LIMITED

TEL: 0086-22-24312818 EMAIL: INFO@GDG-PLYWOOD.COM WEB: WWW.GDG-PLYWOOD.COM

HIGH PRESSURE LAMINATED PLYWOOD

Brief Instruction:

High Pressure Laminated Plywood (HP Plywood) is plywood overlaid by Fireproof Laiminates on Face and Back. The HPL is a kind of Muti-Layer of Fusing materials of kraft paper saturated with phenolic resin, and on Top will be the Melamine Saturated Decorative Paper. Compared to nomral Phenolic Film Faced Plywood and Melamine Faced Plywood, HPL plywood have advantages on Function of Fireproof and Oil Resistance.Based on above properties, HPL Plywood are normally used for Kitchen Furnitures making.

Specification:

Face/Back	Core Materials	Glue	Size	Thickness
HPL	Birch/Hardwood/Poplar	WBP / MR&E1 / MR&E2	1220*2440MM	6-30MM

PROCESSED PLYWOOD

Brief Instruction:

Processed Plywood is produced according to clients' request based on Normal Plywood. Depended on the final application of the Plywood, Clients always need to deep-processed when original materials arrived. Always, It waste time, materials, and money. Considering this, we have noticed the enlarging demand of Deep-Processed Plywood processed in origin place. So we invested in machines such as Grooving Machines, Grinding Machines, Laser Cutting Machines. With these equipments We can provide service of grooving, screwhole making, Grinding special edging etc.

Specification:

Contact Infomation

Contact: Export Department Contact Email: info@gdg-plywood.com Webpage: www.gdg-plywood.com Office Tel: 86-22-24312818